



All four castors can be rotated. Two wheels are fitted with a rotation brake and two wheels have a direction brake.

- Mobile kettle on four castors
- Electric tilt
- Easy to use
- Unheated top
- Easy to clean
- 20-100 litres nominal volume



Max 2,2 kg



Error codes *



433-538 mm



WaterLevel Automatic *



*



Options

- Spray gun
- Drain valve/Butterfly valve
- Sieve plate
- Pouring plate
- Measuring rod
- Cooking basket
- Separate lid
- AutoTemp 11 control

See also:

Controls	24-28
Technical details	30-33
Options	34-37
Technical specifications	50-53
Overview	55

A datasheet is available on request.

The mobile kettle

The EasyMobile model is mounted on four castors, giving it a mobility which opens up new possibilities for the use of tilting kettles. It could for example be used to provide temporary additional capacity, or it could be shared between several kitchens/ departments or used to transport prepared food in.

In kitchens where space is at a premium, the kettle could be brought in from a storeroom when the need arises. From there, it could be moved to where the food is to be served and then back again to the kitchen for cleaning. This saves space in the kitchen and gives the kettle more flexibility in terms of its use, without compromising functionality.

The kettle is available with nominal volumes of 20, 30, 40, 50, 60, 80 or 100 litres and is supplied with a lightweight, tight-closing lid made from synthetic material and hinged on the pillar.

EasyMobile model kettles are supplied as standard with AutoTemp 01 control, which includes electric tilt, heating is infinitely variable with a dial and a cold water cock for filling the kettle with water. Water is added to the steam generator using a valve on the back of the pillar.

As an option, the kettle can be supplied with AutoTemp 11 control, which includes electric tilt with TiltBack, digital control and display of the inner kettle temperature, pushbutton-controlled water filling and WaterLevelAutomatic. The control panel is located on an adjustable control box on the pillar.

The EasyMobile is mounted on a solid underframe, enabling it to be moved and tilted safely. A handle and rotating castors make handling the kettle easy. This kettle is only available with electric heating. Power and water connections are located on the back of the pillar.

The working height is 950 mm.